



# POLYUREA MULTI-PURPOSE #2

## KEY BENEFITS



**Extreme Pressure**



**High Temperature**



**Low Temperature**

FEATURING

**LeakLock™  
Grease Cartridge**

[newmoldinnovations.com](http://newmoldinnovations.com)

**DROP POINT: 500°F  
NLGI #2**

NET WT. 14 OZ (397 g)

# NMI

## POLYUREA MULTI-PURPOSE #2

Good for a wide range of products.

- Farm Equipment
- Bearings
- Conveyors
- Automobiles

Minimum Operating Temperature

-10°F

Maximum Operating Temperature

500°F

**KEEP OUT OF REACH OF CHILDREN**

**Hazard Statements:** Causes serious eye damage. Harmful to aquatic life with long lasting effects.

**Precautionary Statements:**

**Prevention:** Wear eye or face protection. Avoid release to the environment. Wash hands.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

**Storage:** Not applicable.

**Disposal:** Dispose of contents and container in accordance with all local, regional, national, national and international regulations.



**Kentucky Manufacturing Facility**  
824 KY Hwy 356 South • Cynthia, KY 41031