



POLYUREA MULTI-PURPOSE #2

KEY BENEFITS



Extreme Pressure



High Temperature



Low Temperature

FEATURING

**LeakLock™
Grease Cartridge**

newmoldinnovations.com

**DROP POINT: 500°F
NLGI #2**

NET WT. 3 OZ (85 g)

NMI

POLYUREA MULTI-PURPOSE #2

Good for a wide range of products.

- Farm Equipment
- Conveyors
- Bearings
- Automobiles

Minimum Operating Temperature	-10°F
-------------------------------	-------

Maximum Operating Temperature	500°F
-------------------------------	-------

KEEP OUT OF REACH OF CHILDREN

Hazard Statements: Causes serious eye damage. Harmful to aquatic life with long lasting effects.

Precautionary Statements:

Prevention: Wear eye or face protection. Avoid release to the environment. Wash hands.

Response: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage: Not applicable.

Disposal: Dispose of contents and container in accordance with all local, regional, national, national and international regulations.

Kentucky Manufacturing Facility

824 KY Hwy 356 South

• Cynthiana, KY 41031